

# MATERIAL SAFETY DATA SHEET

Amax Industrial Products  
P.O. Box 577  
East Islip, NY 11730

General Information: 1-800-662-0023  
Chemtel: 1-800-255-3924

REVISION DATE: March 3, 2010  
DATE OF ISSUE: March 4, 2010

## I - Product Identification

### dB Solvent HF-165

PRODUCT CODE: 0387

CHEMICAL FORMULATION: High flash solvent based cleaner/degreaser.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 1

FLAMMABILITY: 2

REACTIVITY: 0

HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

## II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX %	OSHA PEL	ACGIH TLV	EPA 40 CFR:			CAS #
				302	355	372	
d-Limonene	10.0-20.0	N/E	N/E	N	N	N	5989-27-5

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit  
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No  
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).  
355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).  
372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

## III - Physical Data

BOILING POINT (°F): N/D

SPECIFIC GRAVITY (WATER = 1): 0.88

VAPOR PRESSURE (mm Hg): <1.0 @ 20°C

VOC CONTENT (% by weight): 10.0-20.0

VAPOR DENSITY (AIR = 1): N/D

EVAPORATION RATE (WATER = 1): >1.0

SOLUBILITY IN WATER: Insoluble

pH: N/A

APPEARANCE AND ODOR: Clear, colorless liquid; citrus-petroleum distillate odor.

## IV - Fire and Explosion Hazard Data

FLASH POINT (°F): 165

(TEST METHOD): Closed cup

FLAMMABLE LIMITS IN AIR (VOLUME %)

UPPER: N/D

LOWER: N/D

EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should be equipped with full protective gear including self-contained breathing apparatus. Use water spray to cool fire-exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARD: Protect from source of ignition. Solvent vapors may cause flashback.

**V - Reactivity Data**

**STABILITY:** Stable

**INCOMPATIBILITY:** Strong oxidizing agents.

**CONDITIONS TO AVOID:** Heat or open flame

**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may produce oxides of carbon.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** None

**VI - Health Hazard Data**

**ROUTES OF ENTRY** INHALATION: X EYE CONTACT: X SKIN CONTACT: X INGESTION: X

**INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS:** None.

**EFFECTS OF OVEREXPOSURE**

**IF IN EYES:** Moderate to severe irritation, redness and tearing.

**IF ON SKIN:** Irritation, chapping, dermatitis with prolonged or repeated exposure. Contains a possible sensitizer.

**IF SWALLOWED:** Gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration may be a hazard.

**IF INHALED:** Respiratory tract irritation, dizziness, weakness, headache, nausea, and unconsciousness.

**EMERGENCY AND FIRST AID PROCEDURES**

**IF IN EYES:** Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

**IF ON SKIN:** Remove contaminated clothing and launder separately before re-use. Wash with soap and water.

**IF SWALLOWED:** Contact physician or poison control center immediately. Do not induce vomiting.

**IF INHALED:** Remove person to fresh air. Administer artificial respiration if person has stopped breathing. Obtain medical assistance.

**VII - Spill or Leak Protection**

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Ventilate area and remove all sources of ignition. Contain spill. Soak up spilled material with inert absorbent material and place in a properly marked closed container for proper disposal.

**WASTE DISPOSAL METHOD:** Consult local environmental authorities.

**VIII - Special Protection Information**

**RESPIRATORY PROTECTION:** Use with adequate ventilation.

**VENTILATION**

**LOCAL:** Recommended

**MECHANICAL:** Not required

**PROTECTIVE GLOVES:** Chemical resistant.

**EYE PROTECTION:** Safety glasses and/or face shield.

**OTHER PROTECTIVE EQUIPMENT:** Eye wash station.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Store in a cool, dry place, away from heat or open flame.

Wash thoroughly after handling. Keep container tightly closed when not in use. Bound and ground during liquid transfer

**OTHER PRECAUTIONS:** Keep out of reach of children. Do not cut or weld on empty container as it may contain combustible residues.

**IX - Transportation Information (ground transportation only)**

**DOT ID NUMBER:** None

**DOT PROPER SHIPPING NAME:** None

**DOT CLASS:** None

**DOT PACKING GROUP:** None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: March 3, 2010

Prepared by: Technical Dept.

DATE OF ISSUE: March 4, 2010

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Amax Industrial Products assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.