

MATERIAL SAFETY DATA SHEET

Amax Industrial Products
P.O. Box 577
East Islip, NY 11730

General Information: 1-800-662-0023
Chemtel: 1-800-255-3924

REVISION DATE: June 13, 2005
DATE OF ISSUE: June 13, 2005

I - Product Identification

KOOL KUT

PRODUCT CODE: 0303

CHEMICAL FORMULATION: Synthetic cutting fluid.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0
HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX %	OSHA PEL	ACGIH TLV	EPA 40 CFR:			CAS #
				302	355	372	
Triethanolamine	1.00-10.0	N/E	N/E	N	N	N	102-71-6
Alkanolamine	1.00-10.0	N/E	N/E	N	N	N	Mixture
Diethanolamine	<2.00	3 ppm	2 mg/m ³ (skin)	Y	N	Y	111-42-2

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).
355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).
372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): N/D SPECIFIC GRAVITY (WATER = 1): 1.06
VAPOR PRESSURE (mm Hg): N/D VOC CONTENT (% by weight): <1.0
VAPOR DENSITY (AIR = 1): N/D EVAPORATION RATE (WATER = 1): N/D
SOLUBILITY IN WATER: Soluble pH: 9.50-10.20
APPEARANCE AND ODOR: Clear, golden-brown liquid, slight odor.

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): > 200 (TEST METHOD):
FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: N/D LOWER: N/D
EXTINGUISHING MEDIA: Water, foam, carbon dioxide, dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.
UNUSUAL FIRE AND EXPLOSION HAZARD: None

V - Reactivity Data

STABILITY: Stable**INCOMPATIBILITY:** Acids and strong oxidizers.**CONDITIONS TO AVOID:** None**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may produce oxides of carbon and nitrogen.**HAZARDOUS POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID:** None

VI - Health Hazard Data

ROUTES OF ENTRY **INHALATION:** **EYE CONTACT:** X **SKIN CONTACT:** X **INGESTION:** X**INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS:** None**EFFECTS OF OVEREXPOSURE****IF IN EYES:** Moderate to severe irritation, tearing and redness. Possible corneal injury.**IF ON SKIN:** Irritation and redness with prolonged exposure.**IF SWALLOWED:** Irritation of gastrointestinal tract, nausea, vomiting.**IF INHALED:** May cause irritation to respiratory tract, dizziness.**EMERGENCY AND FIRST AID PROCEDURES****IF IN EYES:** Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.**IF ON SKIN:** Wash with soap and water. If irritation persists, obtain medical attention.**IF SWALLOWED:** Contact physician or poison control center immediately. Give affected person 1 to 2 glasses of water. Do not induce vomiting unless told to do so by a physician or poison control center. Never give anything by mouth to an unconscious person.**IF INHALED:** Remove person to fresh air. If irritation persists, obtain medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate area and remove all sources of ignition. Contain spill. Soak up spilled material with inert absorbent material and place in a properly marked closed container for proper disposal.**WASTE DISPOSAL METHOD:** Consult local environmental authorities.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation. Do not breathe vapors or mists. If recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.**VENTILATION****LOCAL:** Recommended**MECHANICAL:** Not required**PROTECTIVE GLOVES:** Chemical resistant.**EYE PROTECTION:** Safety glasses.**OTHER PROTECTIVE EQUIPMENT:** Protective clothing.**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Store in a cool, dry place away from heat or open flame. Keep container tightly closed when not in use. Keep away from acids.**OTHER PRECAUTIONS:** Keep out of reach of children.

IX - Transportation Information (ground transportation only)

DOT PROPER SHIPPING NAME: None**DOT CLASS:** None**DOT ID NUMBER:** None**DOT PACKING GROUP:** None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: June 13, 2005**Prepared by:** Technical Dept.**DATE OF ISSUE:** June 13, 2005

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Amax Industrial Products assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.