

MATERIAL SAFETY DATA SHEET

AMAX Industrial Products
PO Box 577
East Islip, NY 11730-0577

GENERAL INFORMATION NUMBER: 1-800-662-0023
CHEMTEL: 1-800-255-3924

REVISION DATE: May 21, 2008
DATE OF ISSUE: March 13, 2009

I - Product Identification

Amax Solvent Cleaner 378GE

PRODUCT CODE: 0381

CHEMICAL FORMULATION: Citrus based degreaser.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 1 FLAMMABILITY: 2 REACTIVITY: 0
HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX	OSHA	ACGIH	EPA 40 CFR:			CAS #
	%	PEL	TLV	302	355	372	
d-Limonene	> 90.0	N/E	N/E	Y	N	N	5989-27-5

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).
355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).
372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°C): 175.5-176 SPECIFIC GRAVITY (WATER = 1): 0.84
VAPOR PRESSURE (mm Hg): 2.0 VOC CONTENT (% by weight): > 90.0
VAPOR DENSITY (AIR = 1): N/D EVAPORATION RATE (WATER = 1): > 1.0
SOLUBILITY IN WATER: Insoluble pH: N/A
APPEARANCE AND ODOR: Clear, reddish-orange liquid; citrus odor.

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): 115 (TEST METHOD): Closed cup
FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: 6.1 LOWER: 0.7
EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should be equipped with full protective gear including self-contained breathing apparatus.
UNUSUAL FIRE AND EXPLOSION HAZARD: Use water spray to cool fire-exposed containers. Solvent vapors may cause flashbacks. Guard against spontaneous combustion of improperly disposed oily rags.

V - Reactivity Data

STABILITY: Stable**INCOMPATIBILITY:** Strong oxidizing and acidic agents, peroxides, halogens, vinyl chloride, and iodine pentafluoride.**CONDITIONS TO AVOID:** Heat, sparks or open flame.**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may yield oxides of carbon.**HAZARDOUS POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID:** None

VI - Health Hazard Data

ROUTES OF ENTRY **INHALATION:** **EYE CONTACT:** X **SKIN CONTACT:** X **INGESTION:** X
INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None
EFFECTS OF OVEREXPOSURE**IF IN EYES:** Moderate to high irritation, redness, tearing.**IF ON SKIN:** Irritation, drying, defatting, dermatitis with repeated or prolonged contact. Contains a potential skin sensitizer.**IF SWALLOWED:** Harmful if swallowed. Gastrointestinal irritation, nausea, vomiting, diarrhea.**IF INHALED:** Irritation of the nose, throat and respiratory tract, coughing and headache.**EMERGENCY AND FIRST AID PROCEDURES****IF IN EYES:** Remove contacts, if applicable. Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.**IF ON SKIN:** Remove contaminated clothing and launder before re-use. Wash with large amounts of water and soap. If irritation persists, obtain medical attention.**IF SWALLOWED:** Call a physician or poison control center immediately. Do not induce vomiting. Rinse mouth with water, and then drink one glass of water. Never give anything by mouth to an unconscious or convulsing person.**IF INHALED:** Remove person to fresh air. If irritation persists, obtain medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate area and extinguish all sources of ignition. Contain spill. Soak up with inert absorbent and place in a properly labeled closed container for disposal.**WASTE DISPOSAL METHOD:** Consult local environmental authorities.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation.**VENTILATION****LOCAL:** Recommended**MECHANICAL:** Not required**PROTECTIVE GLOVES:** Chemical resistant gloves.**EYE PROTECTION:** Safety glasses or chemical goggles.**OTHER PROTECTIVE EQUIPMENT:** Protective clothing, eye wash and shower station.**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Store in a cool, dry place, away from heat or open flame. Keep container tightly closed when not in use.**OTHER PRECAUTIONS:** Keep out of reach of children. Do not cut or weld on empty containers as they may contain combustible residue.

IX - Transportation Information (ground transportation only)

DOT ID NUMBER: None**DOT PROPER SHIPPING NAME:** None**DOT CLASS:** None**DOT PACKING GROUP:** None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: May 21, 2008

Prepared by: Technical Dept.

DATE OF ISSUE: March 13, 2009

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. AMAX Industrial Products assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.